

Page 26, line 17: replace the word "stall" with --stalls--;

Line 19: insert a period after "(worst one)".

Page 27, line 3: delete the word "the" after the word "from".

Page 28, lines 13-14: revise as follows:

A first level comprises basic decoders [882 (]from pending accesses or current accesses)]. [These d] Decoders 882 are the same as decoders 880 in the register files but are applied on the pending signals.

Page 29, line 14: replace "890" with ~~834~~--,

Line 20: replace "822-828" with ~~822, 824, 826, 828~~--.

Page 30, line 19: replace "1750" with ~~1450~~--.

Page 32, line 15: replace "1720" with ~~1720a~~--;

Line 17: replace "1721" with ~~1460~~--;

Line 23: insert ~~coefficient~~ signals 1461,-- after "1462";

Line 24: replace "1721" with ~~1460~~--.

Page 33, line 1: replace "2010" with ~~2002~~--;

Line 2: replace "2012" with ~~2004~~ and replace "2014" with ~~2006~~--.

Page 34, line 5, insert --via signal 2204-- after "2200";

Line 6: replace "2210" with ~~2208~~--.

Line 19: replace "2010" with ~~2002~~--; replace "2012" with ~~2004~~;

Line 20: replace "2014" with ~~2006~~--;

Line 21: replace "2012" with ~~2004~~;

Line 22: replace "2014" with ~~2006~~--;

Line 23: replace "2012" with ~~2004~~.

Page 35, line 10: insert --are-- after "effects."

Page 36, line 7: insert --by-- after "resolved".

Lines 20: insert --by-- after "resolved."

Page 37, line 5: replace "2612" with ~~2602~~--;

Line 13: insert --by-- after "resolved".

Page 38, line 8: insert ~~889~~ after "control signals".

Page 40, line 25: replace "11" with ~~15~~--;

Lines 23 and 24: replace "Figure 17" with ~~Figure 31~~--.